

GYM FLOOR COVERS INSTALLATION, REMOVAL AND STORAGE INSTRUCTIONS

Installation:

1. Storage rack should be moved into appropriate position for cover section removal. The two locking casters shall be locked and the safety clips on selected roller should be completely pulled back.
2. Two people, one at each end of the rack, shall install cover section by gripping end of cover and walking length of floor at a steady pace. DO NOT RUN WITH THE SECTIONS.
3. After unlocking the casters, rack should be moved to next position, repeating steps 1-2 until all sections are installed.
4. All cover sections shall be pulled flat. All overlapped sections should be taped down, using Covermaster's seaming tape.

Removal:

1. All debris and dirt should be swept off the cover and all spills should be damp mopped.
2. All seaming tape shall be removed.
3. With rack in place, casters locked, and safety clips pulled back, cover section should be attached to roller with clips, which are provided.
4. After both persons have installed hand cranks, cover shall be rolled up with each person using one hand to crank and one hand to guide the cover section. Covers should be rolled up from the bottom rollers to the top, never from the top rollers to the bottom. If optional power winder is used, one person will operate power winder and guide cover section, while second person guides the cover section only.
5. Safety clips shall be pushed back on pins to lock roller. Unlock casters and move rack to next position, repeating steps 3-5 until all sections are removed.

Storage:

1. It is important that the gym floor cover system be stored in a clean and dry environment.
2. Do not store anything on storage rack system except for intended product.
3. Always make sure that all safety clips on the rollers are in the locked position during transportation and storage. Casters should always be locked during installation, removal and storage of the gym floor cover.